

PORTABLE POWER STATION

Over voltage
protection



Low voltage
protection



Over load
protection



Over temperature
protection



300W-A Portable power station



Technical parameters

Model	CND-S300W
Type	The lithium battery
Battery Capacity	20Ah 14.8V 296Wh
Full Charge	Around 6.5 hours
USB Output	USB - A2/A3 5V 2.4A
DC Output	DC19V 3.4A
AC Output	220V 60Hz,300W
Weight	3.4kg
Dimension	215*158*162mm
Service Life	More than 1000 cycles
Operating Temperature	0 - 45°C
Charging Temperature	0 - 45°C
Guarantee	12 months

300W-B Portable power station



Technical parameters

Model	CND-S300W
Type	The lithium battery
Battery Capacity	20Ah 14.8V 296Wh
Full Charge	Around 6.5 hours
USB Output	USB - A2/A3 5V 2.4A
DC Output	DC19V 3.4A
AC Output	120V 60Hz,300W
Weight	3.4kg
Dimension	215*158*162mm
Service Life	More than 1000 cycles
Operating Temperature	0 - 45°C
Charging Temperature	0 - 45°C
Guarantee	12 months

500W-A Portable power station



Technical parameters

Model	CND-S500W
Type	The lithium battery
Battery Capacity	34.8Ah 14.8V 51.5Wh
Full Charge	Around 6.5 hours
USB Output	USB - A2/A3 5V 2.4A
DC Output	DC12V 5A
AC Output	220V 60Hz,500W
Weight	5.2kg
Dimension	260*173*170mm
Service Life	More than 1000 cycles
Operating Temperature	0 - 45°C
Charging Temperature	0 - 45°C
Guarantee	12 months

500W-B Portable power station



Technical parameters

Model	CND-S500W
Type	The lithium battery
Battery Capacity	34.8Ah 14.8V 51 5Wh
Full Charge	Around 6.5 hours
USB Output	USB - A2/A3 5V 2.4A
DC Output	DC12V 5A
AC Output	120V 60Hz 500W
Weight	5.2kg
Dimension	260*173*170mm
Service Life	More than 1000 cycles
Operating Temperature	0 - 45°C
Charging Temperature	0 - 45°C
Guarantee	12 months

1000W Portable power station



Technical parameters

Model	CND-S1000W
Type	The lithium battery
Battery Capacity	54Ah 21.6V 11 66.4Wh
Full Charge	Around 6.5 hours
USB Output	USB - A2/A3 5V 2.4A
DC Output	DC24V 5A
AC Output	220V 60Hz, 1000W
Weight	11kg
Dimension	340*236*206mm
Service Life	More than 1000 cycles
Operating Temperature	0 - 45°C
Charging Temperature	0 - 45°C
Guarantee	12 months

1500W Portable power station



Technical parameters

Model	EPE-S1500W
Capacity	1856Whi LiFePO4 8S5P 14.5Ah/cell
DC Input	200W
Support Solar Charge	
Type C1	Input/Output PD100W
AC Output	1500W (230V 50Hz)
Output Wave	Pure sine wave
DC Output	12V/10A
USB-C Output	PD 27W
USB-A1/A2	5V 2.4A*2
USB-A3 &4	QC3.0
Weight	18Kg
Dimension	340*231*276mm

2400W Portable power station



Technical parameters

Model	EPE-S2400W
Capacity	2400Wh LiFeP04
DC Input	360W
Support Solar Charge	
AC Output	2500W (230V 50Hz)
Output Wave	Pure sine wave
DC Output	12V/10A
USB-C 1	Output PD100W
USB-C 2	Output PD 27W
USB-A1/A2	5V2.4A*2
USB-A3 &4	QC3.0
Weight	21Kg
Dimension	500*290*270mm